

One Click™ Melting Point

Simply to the Point



Reliable Results

No need for continuous visual observation. The automatic detection of transmission intensity and digital image analysis replaces time-consuming and error-prone manual measurement.



One Click™ User Interface

The large color display and touch screen with the intuitive One Click™ user interface minimizes training and operator influence. Quick familiarization is guaranteed with the common user interface for all Analytical Laboratory instruments.



Maximum Efficiency

Simultaneous measurement of up to 3 samples for melting point/melting range, or up to 2 for slip melting point saves valuable time and effort. Short heating and cooling times allow more analyses to be performed in a shorter period of time.



Video Recorded

Visual data is stored for unattended measurements. The high resolution videos can be conveniently replayed on the instrument at any time, allowing measurement integrity to be verified.



MP55 Melting Point System

Everything needed for the simple and automatic determination of melting and slip melting points. The MP55 is the ideal starter model and offers far more than can be expected from a standard melting point device:

- One Click™ melting and slip melting point
- Simultaneous determination of up to 3 melting point/melting range or 2 slip melting point samples
- VGA color touch screen
- Video recording
- Compact printer

MP55 Functionality Overview

Applications	Fully automatic melting point (MP), melting range (MR) and slip melting point (SMP) determination. Pharmacopeia measurement mode
One Click™	12 shortcuts
Documentation	USB-P25 compact printer
User Identification	30 different users with full functionality access
Methods and Results	Template for automatic MP, MR and SMP detection Statistics: mean value, standard deviation, difference, outlier result exclusion possible Maximum number of results: 10 Video storage and replay on instrument (with intensity curves) 60 min video run time, stored on instrument
Calibration and Adjustment	Fully automatic optics adjustment (position and brightness) One- and two-point temperature adjustment, automatic calculation of adjustment parameters. VPac pre-filled, ready-to-use capillaries filled with certified reference substances for temperature calibration and adjustment (optional)
Languages	User interface in English, German, French, Spanish, Portuguese, Chinese, Russian, Japanese. Printout in English, German, French
Standard compliance	www.mt.com/mpdp-norms

MP55 Technical Specifications

Temperatures	Measurement range	Ambient – 300 °C
	Heating rate	0.1 – 20 °C/min
	Resolution	0.1 °C
	Heating time (50 to 300 °C)	3 min
	Cooling time (300 to 50 °C)	4 min
Environment	Ambient temperature	10 – 35 °C
	Atmospheric humidity	Max 80% at 31 °C
Dimensions	Width x depth x height / weight	18 x 35 x 19 cm / 4 kg
	Capillaries	MP: 3 (< 1.8 mm o.d.) SMP: 2
Terminal	5.7" VGA color display with touch screen	
	Video: color AVI, 6x magnification	
Communication	USB host (printer, memory stick, barcode reader, hub, keyboard, mouse): 3	
Accuracy Melting Point*	Ambient – 200 °C	+/- 0.2 °C
	200 – 300 °C	+/- 0.5 °C
Repeatability Slip Melting Point*		+/- 0.2 °C

* Subject to sample, environment and handling

Mettler-Toledo GmbH, Analytical

CH-8603 Schwerzenbach,
Switzerland

Tel. +41 44 806 77 11
Fax +41 44 806 72 40

Subject to technical changes

© 10/2016 Mettler-Toledo GmbH, 30353648
Global Marcom 1952 PH

www.mt.com/MPDP

Visit for more information